



The most compact sounder in the Asserta Range, the Mini is a rugged unit with a high IP rating. Suitable for use in harsh environments, its low current consumption makes it ideal for either fire systems or use as a general signalling device in industrial applications. Where the Mini is used in secure applications there is an option to add a tamper switch (*supplied as separate module*) so that any interference with the unit can signal an alarm to a security panel.

- 105dB(A) OUTPUT SUITABLE FOR LOCALISED APPLICATIONS
- IP66 PROTECTION SUITABLE FOR MOST ENVIRONMENTAL CONDITIONS
- FIRST AND SECOND FIX INSTALLATION
- 32 USER SELECTABLE ALARM TONES TO AVOID CONFUSION WITH OTHER SIGNALS
- 2 ALARM STAGES TO PROVIDE STATUS SIGNALLING

Specification

Voltage	9 - 60Vdc 110 - 230Vac
Current	13mA @ 24Vdc (Typical Tone 3) 20mA @ 230Vac (Typical Tone 3)
Sound Output	105dB (Typical Tone 3)
Tones	32
Alarm Stages	2
Monitoring	Reverse Polarity (dc version)
Temperature	- 25°C to + 70°C
Protection	IP66
Construction	ABS
Weight	0.30Kg (dc version) 0.36Kg (mains version)
Colour	Red or grey